

# Washer extractor

## WS6-11



### Exceptional savings and effortless use



### Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

Compass Pro® microprocessor offers:

- Easy program selection
- Language selection
- Quick selection and option buttons for the most frequently used wash programs and options
- Wash program packages optimized on Economy, Performance and Time



### Long-term savings

Extremely low water and energy consumption – see table below

- Automatic Savings weighs the linen and adjusts the water level to the amount of linen, saving water and energy at less than full load
- High extraction force for efficient dewatering
- Super Balance guarantees the correct extraction force



### Pure control

Monitoring of the status of the equipment and performance from anywhere, allowing to take action to improve the business

- Washers connectable to OnE Laundry, the personal assistant for hygiene validation, process management and revenue management



### Global Advanced Hygiene

Global Advanced Hygiene program package<sup>I</sup> with proven log 6 reduction<sup>II</sup> disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

I. Programs available in the standard library of all products, excluding products for specific segments where water temperature is not controllable.

II. Log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data.



Images shown are a representation of the product only and variations may occur.

## Main options and accessories

- Automatic liquid detergent supply (optional I/O board)
- Savings on chemicals with help of Efficient dosing, both ED peristaltic pumps and ED Venturi
- Connection to booking- /payment- system or coin meter

Main specifications		WS6-11			
Rated capacity, filling factor 1:9	kg/lb	11 / 25			
Drum, volume	litre	105			
Drum, diameter	ø mm	595			
Extraction	rpm	776			
G-factor		200			
Standard heating alternatives	electricity, kW	7.5 / 10.0			
Low energy heating alternatives	electricity, kW	3.0			
	steam	x			
	non-heated	x			
<b>Consumption data "Normal 60°C"<sup>1</sup></b>		El		Steam <sup>2</sup>	
		Full load, 11 kg	Half load, 5.5 kg <sup>3</sup>	Full load, 11 kg	Half load, 5.5 kg <sup>3</sup>
Total time	Min	48	45	48	45
Water consumption (cold+hot)	litre	67+19	38+10	86+0	48+0
Energy consumption (motor/heating/hot water)	kWh	0.15/0.55/1.2	0.15/0.3/0.65	0.15/-	0.15/-
Steam consumption	kg	-	-	2.6	1.4
Residual moisture	%	58	66	58	66

1. Water temperature 15°C cold water and 65°C hot water.

2. Depending on steam pressure.

3. Programs with AS.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated	220-240V 1/1N-	50/60	3.0/7.5/10.0	3.5/7.9/10.4	16/35/50
	220-240V 3-	50/60	3.0/7.5/10.0	3.5/7.9/10.4	16/25/32
	380-415V 3/3N-	50/60	3.0/7.5/10.0	3.4/7.9/10.4	10/16/16
	440V 3-	50/60	7.5/10.0	7.9/10.4	16
	480V 3-	60	10.0	10.4	16
Non heated/Steam heated	208-240V 1/1N-	50/60	1	0.8	10
	380-480V 1-2	50/60	1	0.8	10

1. Total power and recommended fuse does not depend on the heating power in those cases.

2. Prepared for 3-

Water and steam connection		WS6-11
Water valves	DN	20
Water pressure	kPa	200-600
Capacity at 300 kPa	l/min	20
Drain valve	ø mm	75
Draining capacity	l/min	170
Steam valve	DN	15
Steam pressure	kPa	300-600
Liquid detergent supplies		5

Floor requirements		
Frequency of the dynamic force	Hz	12.9
Floor load at max extraction	kN	1.9 ± 4.4

Sound levels		
Sound power/pressure level at extraction <sup>1</sup>	dB(A)	69/54
Sound power/pressure level at wash <sup>1</sup>	dB(A)	61/47

Heat emission	
% of installed power, max	5

Shipping data <sup>2</sup>		
Weight	net, kg	152
Shipping volume	m <sup>3</sup>	0.88

Accessories	
Steel base	x
Hose kits for water or steam	x
Fluff collector	x

- |                          |                            |
|--------------------------|----------------------------|
| 1. Operating panel       | 6. Re-used water           |
| 2. Door opening ø 365 mm | 7. Drain valve             |
| 3. Detergent box         | 8. Liquid detergent supply |
| 4. Cold water            | 9. Electrical connection   |
| 5. Hot water             | 10. Steam connection       |

1. Sound power levels measured according to ISO 60704.

2. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Front and side panels in silver grey and dark blue (color samples can be ordered on part number 472998313).

